



F21 Transmisor (solo) 6 botones , 1 Velocidad

Especificaciones Técnicas

Channels	6	Control Speed	1 Speed
Transmitter Emergency Stop	Yes	Codigo FCC	2AZMK-Q1212
Fuente de Alimentación del Transmisor	2 AA batteries	Distancia de Control	300 ft up to 600 ft with optional antenna
Código de Seguridad	32 bits (4.3 billion)	Potencia del Transmisor	≤10dBm
Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Normas	FCC and OSHA standard 1910.179	Garantía	1 Year



MODEL: F21-E2
ITEM CODE: 921-006-002
Dimensions: 156 x 61 x 51 mm
Weight: 255g (without batteries)

Product Features:

- 8 operation buttons, 6 single-speed buttons and "STOP"
- 8 control contactors.
- With battery voltage warning device, the power supply is cut off during low power.
- Program the button function by computer interface.
- Up/Down, East/West, North/South can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.



Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- Operation and maintenance manual.

Standard Configuration:

1. Unique 32 bits ID Code
2. Hamming code
3. Enhanced watch-dog circuit
4. With FCC and CE certificate



Peso & Dimensiones

Peso Total

1 lbs / 1 Kg

Referential Images / Imágenes Referenciales

Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso