



## **GAS-POWERED PULLING WINCH. MAX. PULLING FORCE: 1000 KG Centrifugal Clutch - Including Accessories**

### **Especificaciones Técnicas**

<b>Tambor Gira con motor en ralentí</b>	No	<b>Reductor</b>	Aluminium alloy. Heat treated 3-stage helical & spur gears. Mounted on ball bearings. Oil bath lubrication.
<b>Sistema de Retención de Cuerda</b>	Quick release automatic anti roll-back mechanism (ARM)	<b>Capacidad de Carga</b>	Pulling Single Line: 2200 lb / 1000 kg Pulling Double Line: 4400 lb / 2000 kg Not for Lifting - No apto para Izaje
<b>Velocidad /min</b>	44 ft/min   13.4 m/min	<b>Numero de Velocidades</b>	1 Speed
<b>Marca y modelo del motor</b>	Honda GX50	<b>Tipo de Motor</b>	4-stroke - 360° inclinable - air-cooled   50 cc
<b>Potencia Motor</b>	1.47 kW   2.0 HP	<b>RPM Motor</b>	7000 rpm
<b>Tipo Transmisión / Reductor</b>	Centrifugal	<b>Relación de Transmisión</b>	200:1
<b>Freno al Reductor</b>	Anti-reversing roller clutch bearing	<b>Cable Recomendado</b>	Fiber Ø 3/8" (10 mm)
<b>Tipo de Tambor</b>	Capstan   Cabrestante	<b>Normas</b>	CE
<b>Fabricado en</b>	Canada	<b>Garantía</b>	1 Year
<b>BD ø Diámetro Tambor</b>	Standard: Ø 3" (76 mm) 44ft/min   13.4 m/min Single line No optional drum		

## Detalles del Empaque

<b>A Altura Total</b>	12
<b>D Depth</b>	12.01
<b>W Ancho</b>	17.01

Referential Images / Imágenes Referenciales  
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso