



**2 ton Electric Chain Hoist w/ Power  
Trolley 1 Speed 208~240V 3 $\phi$  1/2 $\phi$  1/2  
60HZ 16ft G100 Nickel Duty H4/M5**

## Especificaciones Técnicas

<b>Capacidad de Carga</b>	2 ton	<b>Altura de Izaje Estandar (Customizable)</b>	16 ft / 5 m
<b>Velocidad /min</b>	26,77 ft @60Hz 6,8 mt @50Hz	<b>Numero de Velocidades</b>	1 Speed
<b>Voltaje</b>	3 Phase 208~240V 50/60Hz	<b>Clase de Servicio</b>	H4/M5/2m/Class D
<b>Freno Motor</b>	Yes	<b>Protección IEC Motor</b>	IP55
<b>Control</b>	Pendant Control IP66	<b>Voltaje del Control</b>	24V
<b>Tipo Transmisión / Reductor</b>	Spur gearbox	<b>Tipo de Cadena</b>	G100 Nickel
<b>Dimensiones de la Cadena</b>	10 mm	<b>Caidas de Cadena</b>	1
<b>Longitud de cadena</b>	16	<b>Humedad</b>	20%~90%
<b>Temperatura</b>	-4 ~ 104° F / -20 ~ 40° C	<b>Potencia del Trolley</b>	500
<b>Velocidad del Trolley /min</b>	43,296 ft @60Hz 11 mt @50Hz	<b>Cantidad de Velocidades</b>	1
<b>Normas</b>	ASME HST-1 , ASME B30.16 , B30.17 , EN60204-34	<b>Garantía</b>	3 Year
<b>Hoist Contactors Amps</b>	25A	<b>Hoist Contactor Brand</b>	sokar
<b>Hoist Contactor Model</b>	CJX2-2511	<b>Hoist Contactor Coil Voltage</b>	24 V
<b>IEC Hoist IP Protection</b>	IP55	<b>Pendant Control Yes No</b>	Yes
<b>IEC Pendant Control Protection</b>	IP66	<b>Pendant Control Emergency Stop</b>	Yes
<b>Pendant Control total Length</b>	13 ft	<b>Hoist Motor Power in KW</b>	3
<b>Hoist Motor Insulation Grade</b>	F	<b>Recommended Hoist Protection Circuit Breaker AMPs and Type</b>	Type D 33A at 240V
<b>Optional Load Chain Brand &amp; Country of Origin</b>	FEC Japan or RUD Germany	<b>Reducer Lubrication Type</b>	Oil
<b>Paint Specifications</b>	Electrostatic Sprayed Plastic (ESP) Epoxy resins, Polyester Resins, Barium, Pigments	<b>Standards Certified</b>	CE
<b>Trolley Motor Brake Type and DC Voltage</b>	DC170V	<b>Trolley Motor Insulation Grade</b>	F
<b>Trolley Contactors Amps</b>	12A	<b>Trolley Contactors Brand</b>	sokar
<b>Trolley Contactors Model</b>	CJX2-1211	<b>Trolley Contactors Coil Voltage</b>	24 V
<b>Trolley Limit Switches</b>	Yes	<b>Trolley Wheel Diameter</b>	110
<b>Trolley Wheel Material</b>	No. 45 steel	<b>Trolley Minimum Turn Radius</b>	1,5
<b>Trolley Beam Range</b>	3" to 7"	<b>Trolley Beam Extension Kit</b>	up to 12"
<b>Load Chain weight per foot [lbs]</b>	1.47	<b>1st Package Type</b>	Wood Crate

## Peso & Dimensiones

<b>Peso Total</b>	430 lbs / 196 Kg
-------------------	------------------

## Detalles del Empaque

<b>H Altura Muerta</b>	23.62
------------------------	-------

<b>A Altura Total</b>	21.26
-----------------------	-------

<b>D Depth</b>	27.36
----------------	-------

<b>W Ancho</b>	16.54
----------------	-------

<b>J Boca Gancho</b>	2.05
----------------------	------

<b>Peso Total (sin cable o cadena)</b>	280.35
--	--------

Referential Images / Imágenes Referenciales  
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso