



1000 Kg Mini Pro-C Electric 4 mt. Chain Hoist Wireless Milwaukee M18 x 2 Battery Powered Double Brake H3 Duty 16000 FLC

Especificaciones Técnicas

Capacidad de Carga	1000 Kg	Battery	Not Included
EU File	Directive 2006/42/EC Machinery	Full Load Duty Cycles	32000
Hoist Limit Switches	Up and Down	Power Battery Model	2 x Milwaukee M18 (Not Included)
Power Battery Voltage	18V x 2 Tot. 36V	Power Battery Location	Pendant Control and/or Hoist Housing
Pendant Control w/Quick Connector	Yes	Altura de Izaje Estandar (Customizable)	13 ft / 4 m
Velocidad /min	planning up/down 9.85 ft/min	Numero de Velocidades	1 Speed
Voltaje	Milwaukee 18V x 2 = 36V	Clase de Servicio	A2 ED 40% / H3 / M4
Tipo de Motor	Brushless motor	RPM Motor	12500
Freno Motor	Yes	Grado de Aislacion	B
Protección IEC Motor	IP54	Protección Tablero de Control	IP23
Control	Wireless Included. Pendant Optional	Freno al Reductor	Yes
Tipo de Cadena	7 X 21 mm G100	Caidas de Cadena	1
Normas	ASME/ANSI B30.16	Garantía	3 Year
IEC Pendant Control Protection	IP23	Pendant Control total Length	Optional
Wireless Control Yes No	PWYT-W-SET-2C-BM	Hoist Motor Brake Type and DC Voltage	Electronic brake and Mechanical brake
Standards Certified	TÜV Rheinland: EN ISO 12100:2010, EN ISO 12100:2010, EN 60204-32:2008, AfPS GS 2019:01 PAK		

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso